



FibreGrid SlipGrip Anti Slip Roll On Flooring



Product Description

Our SlipGrip® Anti Slip Roll On Flooring is made from aluminium oxide grit, which makes them long-lasting and anti-slip.

There are two finishes – coarse and fine. The choice of which is determined by level of foot traffic. There are also two lengths – 1m x 4.5m or 1m x 9.1m; for small or large projects.

Southern Office: Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP
Northern Office: Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA

Online: www.fibregrid.com
Email: sales@fibregrid.com
Phone: 01440 712722
Fax: 01440 712733



001





Characteristics

- Easy application with self-adhesive backing - simply peel back the adhesive backing and roll down onto the preferred surface
- Long-lasting due to a strong resin-bonded aluminium oxide anti slip grit
- Water resistant and pressure sensitive
- Compliant with Building Regulations and Disability Discrimination Act (DDA) 2005



Suitable Applications

- Inside or outside applications
- Industrial environments
- Commercial environments
- Domestic environments



Suitable Substrates

- Wood
- Concrete
- Stone
- Metal



Preparation

Surfaces should be clean, dry and smooth. Apply to wood, concrete, metal, tiles, terrazzo.

Priming

If your surface is non-porous and dust free, priming isn't necessary. However, dusty/porous surfaces should be primed with our Anti Slip Tape Primer.



Application

Peel off the backing strip to a length of approximately 50mm, which gives you more control than if you peel off too much. Then, firm the product into place with a hand or foot.

Do take care not to stretch the roll.

If you find you've made a mistake, don't worry as this can be peeled off easily immediately after fitting, but ensure you do this straight away.

If you are fitting onto surfaces that may get wet, or are likely to experience heavy traffic, then we recommend you use our Anti Slip Tape Edge Sealer.

Anti Slip Roll should be fitted as per the instructions provided.

Southern Office: Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP
Northern Office: Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA

Online: www.fibregrid.com
Email: sales@fibregrid.com
Phone: 01440 712722
Fax: 01440 712733



001



FIBREGRID



FIBREGRID

Anti Slip Tape Primer

This is ideal for porous or dusty surfaces - simply stir and brush on. Coverage is 2-3m² per 500ml. The appearance when being applied is milky, but it dries clear (in about one hour at 10-15°C).

Make sure you only apply the primer to areas that the products will cover, otherwise dust could settle on exposed primer.

After application, brushes can be washed in water.

Anti Slip Tape Sealer

If you are using the products where moisture could penetrate the tape edge, or in very heavily-trafficked areas; we recommend you apply our Anti Slip Tape Sealer. All you need to do is squeeze the sealer from the tube around the tape edge, this will give extra protection and increase the tape's life.



Application

Downtime

Although these products can be walked on immediately, full adhesion takes 24 hours, so please take care with them during this period and avoid heavy use.

Storage

Keep the product warm and dry before using.

Southern Office: Unit 2, Civic Industrial Estate, Homefield Road Central, Haverhill, Suffolk, CB9 8QP
Northern Office: Kingston House, 3 Walton Road, Pattinson North, Washington, Tyne & Wear, NE38 8QA

Online: www.fibregrid.com
Email: sales@fibregrid.com
Phone: 01440 712722
Fax: 01440 712733



001



FIBREGRID