

Anti Slip Tape Sealer



DESIGN

SUPPLY

FABRICATE

INSTALL



















SlipGrip® Anti Slip Tape Sealer waterproofs your anti slip tapes whilst increasing durability and product life. Edge tape sealer minimises the adverse effects of rigorous use or prolonged or severe exposure conditions by providing water and contaminant-tight seal between a graphic film and substrate.

CHARACTERISTICS

- ✓ Prevents the film from lifting due to environmental exposure or cleaning
- Easy to apply

SUITABLE SUBSTRATES

- ✓ Wood
- ✓ Concrete
- ✓ Stone
- Metal

PREPARATION

Surfaces should be clean, dry and smooth. Apply to wood, concrete, metal, titles, terrazzo.

Priming - If your surface is non-porous and dust free, priming isn't necessary. However dusty porous surfaces should be primed with our Anti Slip Tape Primer.

APPLICATION

Simply squeeze the sealer from the tube around the tape edge.

Allow for 2 hours drying time before walking on the substrate.

MAINTENANCE

Downtime - Although these products can be walked on immediately, full adhesion takes 24 hours, so be gentle with them during this period and avoid heavy use.

Storage - Keep the product warm and dry before using

Anti Slip Tape Primer

Anti Slip Tape Sealer

This is ideal for **porous** or **dusty** surfaces.

Simply stir and brush on. Coverage is 2-3m² per 500ml. The appearance when applied is milky, but it dries (in about one hour at 10-15°C) clear. Make sure you only apply the primer to areas that the products will cover, otherwise dust could settle on exposed primer. After application, brushes can be washed out in water.

If you are using the products where **moisture** could penetrate the tape edge, or in very **heavily-trafficked areas**, then we recommend you apply our Anti Slip Tape Sealer.

All you need to do is squeeze the sealer from the tube around the tape edge. This will give extra protection and increase the tape's life.



These instructions are to be used as a guide. Always employ safe practices. It is recommended to first test the suitability of any product on a small area before carrying out a full application.

www.fibregrid.com email: sales@fibregrid.com Call: 01440 712722 www.fibregrid.com email: sales@fibregrid.com Call: 01440 712722

Fibregrid

Southern Office:
Unit 2, Civic Industrial Estate,
Homefield Road Central,
Haverhill,
Suffolk,
CB9 8QP

Northern Office:
Kingston House,
3 Walton Road,
Pattinson North,
Washington,
Tyne & Wear,
NE38 8QA

www.fibregrid.com

@ Email: sales@fibregrid.com

C Phone: 01440 712722



